



Fujitsu Ethernet Controller 1x1Gbit PCI32 PRO/1000MT Cu Ip 1000 Mbit/s



Brand : Fujitsu

Product code: S26361-F2839-L201

Product name : Ethernet Controller 1x1Gbit PCI32 PRO/1000MT Cu Ip

Ethernet Controller 1x1Gbit PCI32 PRO/1000MT Cu Ip

[Fujitsu Ethernet Controller 1x1Gbit PCI32 PRO/1000MT Cu Ip 1000 Mbit/s:](#)

Eliminate server bottlenecks and migrate existing Category-5 networks to Gigabit Ethernet easily and cost-effectively with the Intel PRO/1000 MT Server Adapter. Featuring flexible, auto-negotiating 10/100/1000 Mbps performance, the Intel PRO/1000 MT Server Adapter is designed to automatically scale with growing networks.

Enhance server performance further by teaming multiple Intel PRO Server Adapters using Intel's expanded advanced server feature software to achieve multi-Gigabit scalability and redundant failover capability. With a flexible design that fits almost any type of PCI bus, the standards-based management features and wide network operating system support help to ensure extensive compatibility with the latest server and networking environments.

Fujitsu Ethernet Controller 1x1Gbit PCI32 PRO/1000MT Cu Ip. Connectivity technology: Wired, Host interface: PCI. Maximum data transfer rate: 1000 Mbit/s

Ports & interfaces		System requirements	
Connectivity technology *	Wired	Compatible operating systems	Microsoft Windows NT 4.0, SunSoft Solaris 7, Novell NetWare 4.2, Novell NetWare 4.11, Novell NetWare 5.1, SunSoft Solaris 8, Novell NetWare 5.0, FreeBSD, Linux 2.2.5 or later, Caldera OpenUnix 8, Novell NetWare 6, UnixWare 7.x, Microsoft Windows 2000/XP
Host interface *	PCI		
Network			
Maximum data transfer rate *	1000 Mbit/s	Minimum processor	Intel 82545EM
Data link protocols	Ethernet, Fast Ethernet, Gigabit Ethernet		
Design		Weight & dimensions	
Form factor	Plug-in	Depth	165 mm
		Height	81 mm
Other features			
Compliance industry standards		IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x, IEEE 802.3ad (LACP), WfM 2.0	
Slot type		PCI-X Hot-Plug 133 MHz	
I/O ports		1 x RJ-45	
Management protocols		SNMP, DMI 2.0	
Dimensions (WxDxH)		165 x 81	
Internal memory		0.64 MB	

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 16-APR-2025. Prints or copies of Information are only valid on the printed Publication date